

# RM Ævo

Capacity

4.0" x 6.5"

10.16 cm x 16.5 cm



The RM Ævo is a new generation of label and film adhesive feeding technology with a print & apply option that elevates state-of-the-art to a whole new level. This is the most accurate model available of 2.0"x2.0" / 5.1 cm x 5.1 cm.



The recognized leader in adhesive component placement technology

# RM Aëvo

Capacity

4.0" x 6.5"

10.2 cm x 16.5 cm

## Features

- AccuPlace's proven peeling technology process for ultimate accuracy and process reliability
- Minimal mechanical adjustments ensure easy setup and component changeover
- Rollerless drive technology means higher accuracy, lower maintenance, and longer life
- No tools required for routine maintenance
- Advanced clean room options for ultra-clean environments
- Simple material threading ensures quick roll replacements
- High precision construction for lasting quality

## Print & Apply

- Zero-queue printing for serialized printing
- 300 dpi or 600 dpi available
- Very compact printer design, integrated in applicator
- High print quality on even the smallest labels
- Economic in material consumption
- Barcode scanner for print verification can be integrated



## Specifications

Printing Registration Accuracy	± 0.002"/0.05 mm*
Size:	
Depth	528 mm (20.79")
Height	809mm (31.86) (incl. stack indicator)
Width	180mm (7.09")
Weight	63 lbs/28.5 kg (including printer)
Input Voltage	100-240 VZC 50-60Hz 1ø
Current	4A@220V or 8A@115V
Capacity(Label or Component size)	Max 50mm x 50mm x 5 mm thick / 2"x2"x.02" LxWxH
Label Roll Capacity	ø430mm (17") x 60mm (2.36")Liner Width
Label Roll Core Size	Ø76mm (3") or Ø152.4mm (6")
Air Pressure Requirement	75 psi/5 bar
Printing Thermal Media Capacity	Ø.69.85mm (2.75")x60mm (2.36") max. 20mm (0.78") min., core ø 25.4 (1")
Speed	1.5 sec. typical peel & place 2-5 sec. Typical print, peel & place
Clean Room Printing	Possible, requires the correct choice or label stock, ribbon, and core
Ribbon	Wound out thermal transfer ribbon
Print Resolution	300 dpi & 600 dpi
Life Time Print Head	1.0x10 <sup>8</sup> pixel cycles. (For a 300 dpi print head, the lifetime is 333.3" of print length)

\*Component dependent. AccuPlace will evaluate your application upon receiving your parts and specifications.